



# NEW DIMENSIONS SUPREME

**Alkaline Liquid Cleaner Degreaser**  
Product Code No. 10007

**DESCRIPTION:**

**A HIGHLY CONCENTRATED  
MILD ALKALINE LIQUID CLEANER/DEGREASER**

**NEW DIMENSIONS Supreme** is a concentrated all purpose mildly alkaline cleaner and degreaser. Supreme helps to eliminate high disposal costs and problems. It can be used over and over in the same solution effectively. Supreme eliminates highly dangerous vapor systems, makes water “wetter”, penetrate deeper, emulsifies and suspends dirt and soil quicker and is safer and easier to use. Supreme is free rinsing and therefore, leaves no film or residue. After cleaning the surface is often ready for plating, painting or welding with no additional preparation necessary. Supreme has a built-in inhibitor for short term elimination or oxidation.

**FEATURE &  
BENEFITS:**

**Features**

**Benefits**

- |  |   |
|--|---|
| <ul style="list-style-type: none"><li>• Environmentally Safe Liquid</li><br/><li>• Safe on all surfaces (when used as directed)</li><br/><li>• Super Concentrate</li></ul> | <ul style="list-style-type: none"><li>• Contains no chlorinated solvents</li><li>• Contains no petroleum distillates</li><li>• Non-flammable</li><li>• Biodegradable</li><li>• USDA approved</li><li>• General purpose cleaner</li><br/><li>• Free rinsing</li><li>• Built-in corrosion inhibitor</li><li>• Economical</li><li>• Can be used in any type of immersion cleaning equipment or one-shot off-line spray cleaning</li><li>• Effective in hot or cold solutions</li><li>• Degreaser replacement</li></ul> |
|--|---|

**APPLICATIONS:** Supreme is an excellent replacement for vapor degreasers and other ozone depleting cleaning agents. It can be used in soak cleaning tanks, parts washers (mechanical and ultrasonic) or manually with tanks, power scrubbers or spray bottles.

Supreme is safe on steel, chrome, cadmium, bronze, iron, nickel, copper, stainless steel, lead, brass and most alloys. Completely safe on aluminum when used as directed. Also safe on rubber, neoprene, nylon and glass. Safe on painted surfaces when diluted 1 to 5 or more with water.

Supreme is effective in both hot and cold solutions. Cleaning efficiency is increased with agitation (mechanical, ultrasonic, heat). Although it is difficult to recommend an exact cleaning cycle prior to specific application testing, the following cycles can be used as a guideline.

**Heavy Degreasing**

10-35% b/v  
60° - 82° C  
(140° - 180° F)

Heavy oils, greases  
drawing compounds  
and metal working  
lubricants

**General Cleaning**

5-10% b/v  
Ambient - 66° C  
Ambient - 150° F

Salts, oils, grease

**Soak Cleaning**

2-5%  
60° - 82° C  
(140° - 160° F)

Light oils, grease,  
drawing compounds,  
general manufacturing  
soils

Heavy degreasing with Supreme should employ temperature and/or mechanical agitation to remove oil from the immersed part. When cleaning heavy grease, caked-on soils or parts with difficult geometry's, the use of ultrasonic energy will aid in the cleaning process.

For general cleaning, Supreme can be used in hot or cold solutions. Aluminum, steel, cast iron and most other metals can be cleaned in the same concentrations of Supreme without etching the aluminum.

In most applications rinsing of the part is required to remove any remaining contaminants and residual cleaning solution.

For every part to clean there is a proper solution concentration and immersion time for using Supreme. Because it is safe on any washable surface, and is totally water soluble, you should experiment with different concentrations and dwell times. Some method of agitation and heat will always give quicker results.

---

**PHYSICAL  
DATA:**

Ozone depletion potential:	zero
Density:	9.01 lb/gal
Specific gravity:	1.080
Freezing point:	0° C (32° F)
Solubility in water:	Complete

Color:	Blue
Odor:	Mild
Form:	Liquid
pH:	12.8 (concentrate)
Flash point:	N/A

**CONTROL  
PROCEDURE:**

A hand-held refractometer is the recommended method for analysis of Supreme. A refractometer calibrated in "BRIX with a range of 0 to 10" is suitable. The refractometer reading times 5.5 will give an approximate of the concentration.

$$\% \text{ Supreme} = (\text{Refractometer Reading}) \times 5.5$$

Wet analysis of Supreme is as follows:

Indicator -	methyl orange dissolve 1 gram methyl orange into a 1,000 mls of deionized water
Titrant -	0.5N sulfuric acid

1. Take a 25 ml sample of working solution (be careful not to collect any oils, greases from surface)
2. Add 50 mls deionized water
3. Add 10 drops of methyl orange indicator
4. Titrate sample with 0.5N acid to pink end point
5. % Supreme b/v = mls of 0.5N acid x 3.1

An automatic control system is also available for continuous analysis and replenishment. Contact your MacDermid representative for additional details.

**SAFETY &  
WARNING:**

MacDermid, Inc. recommends that the company/operator read and review the MacDermid Material Safety Data Sheets for the appropriate health and safety warnings before use.

**Material Safety Data Sheets are available from MacDermid Incorporated.**

**WASTE  
TREATMENT:**

Prior to using any recommendations or suggestions by MacDermid, Inc. for waste treatment, the user is required to know the appropriate local/state/federal regulations for on-site or off-site treatment which may require permits. If there is any conflict regarding our recommendations, local/state/federal regulations take precedent.

To separate greasy, oily contaminants from a used Supreme emulsion, the pH of the spent solution should be dropped to between 6.5-7.5 with muriatic acid (consult your supplier for proper handling and treatment procedures) and then allowed to sit

in a still tank for up to 36 hours. After the material has been released and has risen to the surface, it can be skimmed from the top. The oily waste material can then be drained off and disposed of as hazardous waste. The spent cleaning solution can then be disposed of through an effluent waste water disposal system.

---

<b>ORDER INFORMATION:</b>	<b><u>Product</u></b>	<b><u>Product Code</u></b>	<b><u>Container</u></b>
	NEW DIMENSIONS Supreme	10007	330 gal tote 55 gal drum 5 gal pail

Page 4 of 4 - 2/2/99  
New Dimensions Supreme  
Alkaline Liquid Cleaner Degreaser

---

Also read carefully warning and safety information on the Material Safety Data Sheet. This data sheet contains technical information required for safe and economical operation of this product. READ IT THOROUGHLY PRIOR TO PRODUCT USE. **Emergency directory assistance** Chemtrec 1-800-424-9300.

DISCLAIMER: All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. No statement or recommendation shall constitute a representation unless set forth in an agreement signed by officers of seller and manufacturer. NO WARRANTY OR MERCHANTABILITY OR WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS MADE. The following warranty is made in lieu of such warranties and all other warranties, express, implied, or statutory. Products are warranted to be free from defects in material and workmanship at the time sold. The sole obligation of seller and manufacturer under this warranty shall be to replace any product defective at the time sold. Under no circumstances shall manufacturer or seller be liable for any loss, damage or expense, direct or consequential, arising out of the inability to use the product.

Notwithstanding the foregoing, if products are supplied in response to a customer request that specifies operating parameters beyond those stated above, or if products are used under conditions exceeding said parameters, the customer by acceptance or use thereof assumes all risk of product failure and of all direct, indirect and consequential damages that may result from use of the products under conditions, and agrees to exonerate, indemnify and hold harmless MacDermid Incorporated therefrom.

No suggestion for product use nor anything contained herein shall be construed as a recommendation to use any product in infringement of any patent rights, and seller and manufacturer assume no responsibility or liability for any such infringement.